

Phone: 800-558-5986 Fax: (262) 767-2529 Direct: +1 (262) 763-0147 www.ldvusa.com

PRELIMINARY SPECIFICATIONS FOR:

Corona Fire Department (CA)

RFP No. 18-009SB:
Corona Fire Department Hazmat Trailer

LDV MODEL # T24HMR-33830-17

DATE July 19, 2018 REV1 June 25, 2018



Phone: 800-558-5986 Fax: (262) 767-2529 Direct: +1 (262) 763-0147 www.ldvusa.com

TABLE OF CONTENTS

DC ELECTRICAL SYSTEM:	.6
MISCELLANEOUS OTHER:	.6



Phone: 800-558-5986 Fax: (262) 767-2529 Direct: +1 (262) 763-0147 www.ldvusa.com

PRICING PAGE:

Total commercial price per unit as specified, FOB Origin \$107,968.00

Discount amount -\$6,478.00

Commercial discounted price as specified \$101,490.00

Delivery charge to Corona FD (CA), or nearby

\$2,900.00

Total price per unit

\$104,390.00

Delivery terms: Ask your Sales Representative

Payment Terms: Net 30

Quote is firm for 90 days from RFP close

Quoted price does not include any applicable FET, federal, state or local tax unless specified.



Phone: 800-558-5986 Fax: (262) 763-0156 Direct: +1 (262) 763-0147 www.ldvusa.com

Item	Qty	www.idvusa.com
1.00	<u> </u>	TRAILER:
1.01	1	ATC Quest Aluminum Trailer. 14,000 GVWR tandem axle trailer, 8.5'W x 24'L x 7'H
		FRAME:
		• Full perimeter aluminum frame (All-tube construction)
		• Torsion axles (2) axle - 7000# - torsion - ez lube hubs - electric brakes ground clearance:
		standard (approx. 14.25" - no load)
		Axle spacing - spread axle
		• All tube construction
		• Tongue - extended triple tube - 12"
		• 2-5/16" coupler with Safety chains & hooks
		3500# 12v electric tongue jack 16" o/c floor crossmembers
		• 16
		• 16" o/c wall supports .125
		• Flat floor design
		Frame protection - skid plates
		Tank - fuel - diesel - 24 gallon - end fill - in frame
		• Truck plug - 7 way - j-560
		Jack - stabilizer - scissor - 24" - 5000# location: (1) pair front & (1) pair rear
		• Tire/wheel (5) - ST235/88R16/LRG - radial on grey mod
		• Spare tire mount - exterior wall - 8 lug
		Spare the meant section half chag
		EXTERIOR:
		Smooth alum. Radius wheel boxes
		Flat front design
		Gravel guard - atp - 24" - with j rail
		• 36" x 78" side door - 405 series
		.050 aluminum screwless exterior - Red
		One-piece aluminum roof
		Door - entrance - 405 series - 32" x 78" - flush lock
		LED clearance lights with LED slim line brake lights
		Awning - 12v with aluminum weathershield - 21' - white - onyx vinyl fabric
		Door - rear ramp - hd premium - continuous aluminum hinge - 3600# rated max load - 6000#
		vehicle load
		Ramp door exterior - rear - color matched

Transition flap - tpo - black coin - 16"IRamp door flooring - rear - tpo - black coin

• Hasp - stainless steel - for cam bars/bar locks on ramp door

-Includes 405 Series Double Doors - Vented

• Generator Compartment - Tongue Mounted - Atp Expanded Metal On Floor Of Compartment

-Includes Galvanized Liner For Front Wall Of Trailer Only Gen Box & Doors Built To Fit

• Door latch - bar lock - aluminum



Phone: 800-558-5986 Fax: (262) 763-0156 Direct: +1 (262) 763-0147 www.ldvusa.com

Item Qty

Specific ---Size Of Gen

- -Does Not Include Insulation
- Battery Compartment Exterior Double Atp

INTERIOR:

- Interior height 7.0'
- Interior ceiling screwless aluminum
- Insulation Ceiling Eps 1" R-3
- Interior walls screwless aluminum
- Insulation Walls Eps 1" R-3
- Flooring Tpo Black Coin
- Smooth aluminum wheel boxes

CABINETS AND COUNTER TOPS:

- (15') Cabinet Aluminum Lower Aluminum Countertop 40"H X 24"D
- (7) Cabinet Aluminum Lower Straight 36"W
- (1) Cabinet Aluminum Lower Straight 48"W
- (23') Cabinet Aluminum Upper 18"H X 14"D W/ Radius Lower Edge Top Hinged Doors and Gas Shocks
- (6) Cabinet Aluminum Wall Mount 36"W X 36"H X 24"D W/ (2) Adjustable Shelves
- (1) Countertop Aluminum Fixed 36"W X 24"D
- (10') Bench Seat W/ Storage Aluminum with 4" bench seat cushion

ELECTRICAL:

- (3) Battery 12v Agm (930 Ca, 775 Cca)
- (1) Breaker Box 50 Amp 6 Space, 12 Circuit Panel 50 Amp Main Breaker
- (1) Switch Power Cut-Off Manual 12v
- (1) Power Inlet Motorbase 50a W/ Shore Cord 25'
- (7) Recept Interior 120v 15a
- (4) Recept Interior 120v 15a USB
- (2) Recept Exterior 120v 15a Gfi Protected
- (6) Light Puck Led 2.75" 12v Non-Recessed under upper cabinets
- (8) 18" LED recessed ceiling lights with switches
- (1) Generator Commercial 8.0 Kw Onan Diesel (120v Only) with remote start and fuel gauge
- (1) Transfer Switch Auto 50a

HVAC:

- (2) A/C W/ Heat Pump 15,000 Btu Low Profile 10.5" Black with wall mounted thermostat
- (2) Roof vent with 12v reversible fans, manual activation;

Note: Trailer specifications are from *Aluminum Trailer Company* and are subject to change without notice.



Phone: 800-558-5986 Fax: (262) 763-0156 Direct: +1 (262) 763-0147 www.ldvusa.com

OI L	CIALTY VEHICLES Www.ldvusa.com
Qty	
	 INDEPENDENCE ONYX INTERIOR: Wall Covering: Polar white aluminum sheeting Ceiling covering: Polar white aluminum sheeting Floor Covering: #150 Onyx PVC Flooring Vinyl Coverings: #WH1-2140 Whisper Black Cabinets: Silver Frost Counters: Aluminum Note: Manufacturer reserves the right to substitute equivalent materials.
	DC ELECTRICAL SYSTEM:
6	Code 3, 79SCENE, 9X7 white LED scene light with chrome flange (or current model)
ŭ	NOTE: Lights controlled by switch mounted inside of entry door.
	EMERGENCY LIGHTING:
6	Code 3 3X7 red LED light head with bezel, 45BZR (or current model).
	NOTE:
	Lights controlled by switch mounted inside of entry door.
6	Code 37X9 red LED light head with bezel, 85BZR (or current model).
	NOTE: Lights controlled by switch mounted inside of entry door.
	MISCELLANEOUS OTHER:
1	Complete manual set, including the following (as applicable): • As-built specifications with interior and exterior drawings as used for production of the vehicle. • Chassis and body owner's manuals. • 12Vdc and 120Vac legends showing wire gauge, color, number and function. • 12Vdc high current wiring diagram illustrating the battery system, isolators, power converters, alternator, disconnect switches and control panels. • Roof top antenna placement drawing and legend identifying antenna placements and termination points. • Audio/Video cabling diagram. • Warranty and Return Authorization procedures. • Chassis and generator maintenance and service logs. • Battery maintenance information. • All individual component manuals and warranty registration cards as provided by component manufacturers. Customer is responsible for completing warranty cards and mailing them to manufacturers.
	LDV warranty, covering 1 year or 12,000 miles for manufacturer's defects in materials and workmanship. Refer to LDV warranty statement for details of warranty coverage.
	Note: Project scope does not include certain tasks or costs that are the responsibility of the customer unless clearly specified as LDV supplied. These items include, but are not limited to: • Radio and telephone system programming. • Activation and service fees for cellular telephones, satellite telephones, satellite TV, satellite internet access. • Loading and configuring computer software. In the event of a discrepancy between the drawing and specification, the specification will supersede. LDV reserves the right to make substitutions of equal quality and specifications of
	Qty 6 6



Phone: 800-558-5986 Fax: (262) 763-0156 Direct: +1 (262) 763-0147 www.ldvusa.com

Item	Qty	
		those listed in this document.
		Some component models change frequently. In the event that a specified component model becomes unavailable at the time LDV attempts to source it, LDV will provide a replacement model with equivalent or better features, as agreed upon with the customer.