



# Project Conditions

## City of Corona

**Project Number: CUP17-003**

**Description: TENNIS CENTER**

**Applied: 5/18/2017**

**Approved:**

**Site Address: 1695 E CHASE DR CORONA, CA**

**Closed:**

**Expired:**

**Status: APPLIED**

**Applicant: PHX ARCHITECTURE**

**Parent Project:**

**15990 N GREENWAY-HAYDEN LOOP #C100  
SCOTTSDALESCOTTSDALE ,85260**

**Details: FULL DESCRIPTION: CUP FOR A 4,077 SQ FT RECREATION BUILDING AND 11 TENNIS COURTS ON 4.98 ACRES.**

LIST OF CONDITIONS	
DEPARTMENT	CONTACT
	Cindi Schmitz
<ol style="list-style-type: none"><li>1. Meet with Corona Fire Department to determine locations of red curbing and signage for fire hydrants, fire department connections, and designated fire lanes on site.</li><li>2. Obtain the following fire department permit(s):Place of Assembly</li><li>3. Per 511 of the Corona Municipal Code, a public safety radio communication study is required. Consult with the Fire Department for specific requirements for this study.</li><li>4. Groves and weed abatement shall be maintained so as not to pose a fire hazard until time of development.</li><li>5. Dead end access drives shall not exceed one hundred fifty (150) feet in length.</li><li>6. Fire extinguishers shall be provided. Fire extinguishers shall bear a California State Fire Marshal's service tag; it shall be appropriately rated for the hazard; it shall be mounted so that the top of the extinguisher is no higher than five (5) feet above floor level; and shall be located such that the travel distance to an extinguisher does not exceed seventy-five (75) feet.</li><li>7. Fire hydrants are to be spaced a maximum 250 feet apart.</li><li>8. Place Fire Department DPR comments on plans as general notes.</li><li>9. Provide Class A roofing material.</li><li>10. Provide plans for two (2) all weather surface access ways to be approved by the Fire Marshal and construct the access way(s) to accommodate 70,000 lbs GVW during all phases of construction.</li><li>11. Provide turn-around for access drive(s) meeting Fire Department standards/approval.</li><li>12. Provide a minimum twenty-five (25) foot inside and fifty (50) foot outside radius for access drive(s).</li><li>13. Required Fire Department access and exit doors shall not be obstructed by parking, landscaping, trash enclosures, etc., nor shall the access and exit obstruct drives.</li><li>14. Plans shall show a minimum drive width of 28 feet.</li><li>15. Private on-site fire hydrants shall be designed and installed in accordance with NFPA standards 24 and 13 and city standards. Private fire hydrants shall be painted rustoleum red or equivalent. Plans shall be submitted through the Building Division for approval.</li><li>16. Storage, use and dispensing of materials shall comply with the current editions of the California Fire &amp; Building Codes.</li><li>17. A fire facilities fee of \$231.00 per acre is required per Corona Municipal Code and must be paid prior to building permit issuance.</li><li>18. A KNOX box or KNOX padlock shall be provided for the building (s) and any existing or proposed perimeter gating/fence as prescribed by the Fire Marshal. Applications for KNOX boxes or KNOX padlocks are available at knox.com.</li><li>19. Street and drive grades shall not exceed 10% unless approved by the Fire Chief and City Engineer.</li></ol>	



# Project Conditions

## City of Corona

Cindi Schmitz

20. Plans of new or modifications to existing fire protection, detection, alarm or monitoring systems shall be reviewed and approved by the Corona Fire Department prior to installation.
21. The fire service waterline shall be looped and provided with two (2) separate points of connection if over 500 lineal feet.
22. The developer shall meet with Corona Fire Department prior to construction to determine the location of: fire department connections for sprinkler systems, post indicator valves, etc. Call (951) 736-2220 for an appointment.
23. All projects shall comply with the City of Corona Fire Department Construction Standard. A copy of which is available at [discovercorona.com](http://discovercorona.com). Projects shall have approved all weather access from two (2) directions and fire hydrants providing the required fire flow tested and accepted prior to combustible construction.
24. A specific address, assigned by the City of Corona, shall be provided for each building. Address must be illuminated during all hours of darkness. See Premise Identification Standard at [discovercorona.com](http://discovercorona.com)
25. At no time shall fire hydrants or fire lanes be blocked by building materials, storage, equipment, and/or vehicles.
26. Any revised site plan shall be submitted to the Fire Department for screen check approval prior to building plan submittal.
27. A minimum fire flow of 3000 gpm shall be provided for commercial structures.
28. A KNOX padlock or KNOX override switch shall be provided for gate(s) in this project. Applications for KNOX Padlock(s) and override switches are available at [knox.com](http://knox.com)
29. A sign showing the occupant load limit(s) shall be posted in a conspicuous place near the main exit from the room.

### BUILDING

1. Plans shall show detectable warnings at accessible paths of travel that cross vehicular ways
2. Plans shall indicate that ramp landings are sized properly (show dimensions on plans.)
3. Plans shall indicate where ramps will be constructed on sloped surfaces and show handrails.
4. Plans shall indicate accessible path of travel that crosses dirt road will be an approved surface.

### PLANNING

1. This permit hereby allowed is conditional upon the privileges being utilized by the securing of the first permit thereof, or compliance with all conditions on the granting of this conditional use permit within two (2) years after the effective date thereof, and if they are not utilized, or construction work is not begun within said time and carried on diligently to completion, this authorization shall become void, and any privilege or permit granted shall be deemed to have lapsed.
2. The project shall comply with all applicable requirements of the Corona Municipal Code (CMC) and ordinances and the relevant Specific Plan, if any, including the payment of all required fees.
3. The applicant or his successor in interest shall comply with the mitigation measures in the Mitigated Negative Declaration prepared for the project.
4. To the fullest extent permitted by law, the applicant shall defend, indemnify and hold the City of Corona and its directors, officials, officers, employees, volunteers and agents free and harmless from any and all claims, demands, causes of action, proceedings, costs, expenses, liabilities, losses, damages or injuries of any kind, in law or equity, in any manner arising out of, pertaining to, or incident to any attack against or attempt to challenge, set aside, void or annul any approval, decision or other action of the City of Corona, whether such approval, decision or other action was by its City Council, Planning and Housing Commission or other board, director, official, officer, employee, volunteer or agent. To the extent that Government Code Section 66474.9 applies, the City will promptly notify the applicant of any claim, action or proceeding made known to the City to which Government Code Section 66474.9 applies and the City will fully cooperate in the defense. The Applicant's obligations hereunder shall include, without limitation, the payment of any and all damages, consultant and expert fees, and attorney's fees and other related costs and expenses. The City shall have the right to retain such legal counsel as the City deems necessary and appropriate.





# Project Conditions

## City of Corona

<b>PLANNING</b>	
<p>5. Nothing herein shall be construed to require City to defend any attack against or attempt to challenge, set aside, void or annul any such City approval, decision or other action. If at any time Applicant chooses not to defend (or continue to defend) any attack against or attempt to challenge, set aside, void or annul any such City approval, decision or other action, the City may choose, in its sole discretion, to defend or not defend any such action. In the event that the City decides not to defend or continue the defense, Applicant shall be obligated to reimburse City for any and all costs, fees, penalties or damages associated with dismissing the action or proceeding. If at any time both the Applicant and the City choose not to defend (or continue to defend) any action noted herein, all subject City approvals, decisions or other actions shall be null and void. The Applicant shall be required to enter into any reimbursement agreement deemed necessary by the City to effectuate the terms of this condition.</p> <p>6. All freestanding and retaining walls shall be constructed of decorative masonry as approved by the Community Development Department.</p> <p>7. Landscape plans shall be submitted to the Building Division as a separate submittal for plan check. At time of submittal, the developer shall submit a plan check and inspection deposit in the amount of \$5,000 to the Planning Division for the landscape plans. This deposit is separate from the Building Division's plan check submittal fees. Any money left remaining from the deposit will be reimbursed to the developer at the completion of the project.</p> <p>8. Signage for the tennis center is allowed per Exhibit I of CUP17-003.</p> <p>9. All landscaping shall be installed per the approved landscape plan prior to issuance of a certificate of occupancy.</p> <p>10. Use of loudspeakers shall be prohibited at the tennis center.</p>	
<b>PUBLIC WORKS</b>	<b>Zachary Murray</b>
<p>1. The developer shall comply with the State of California Subdivision Map Act and all applicable City ordinances and resolutions.</p> <p>2. Prior to recordation or issuance of grading permit, the applicant shall demonstrate to the satisfaction of the Public Works Director that the proposed subdivision will not unreasonably interfere with the use of any easement holder of the property.</p> <p>3. All improvement and grading plans shall be drawn on twenty-four (24) inch by thirty-six (36) inch Mylar and signed by a registered civil engineer or other registered/licensed professional as required.</p> <p>4. The developer shall construct or guarantee construction of the required improvements prior to recordation of the Parcel Map because the construction of the improvements is a necessary prerequisite to the orderly development of the surrounding area.</p> <p>5. All conditions of approval shall be satisfied and the final parcel map prepared and accepted by the City for recordation within 24 months of its approval, unless an extension is granted by the City Council.</p> <p>6. In the event that off-site right-of-way or easements are required for the City of Corona master plan facilities to comply with these conditions of approval, the developer is required to secure such right-of-way or easements at no cost to the City.</p> <p>7. In the event that off-site right-of-way or easements are required for the City of Corona master plan facilities to comply with these conditions of approval, the developer is required to secure such right-of-way or easements at no cost to the City. In the event that the developer requires the City's assistance to condemn said right-of-way or easements, the developer shall enter into an agreement with the City for the acquisition of said right-of-way or easements pursuant to Government Code Section 66462.5, and pay any and all costs, as determined by the City, associated with the condemnation process.</p> <p>8. All existing and new utilities adjacent to and on-site shall be placed underground in accordance with City of Corona ordinances.</p> <p>9. Prior to issuance of a Certificate of Occupancy, the developer shall cause the engineer of record to submit project base line work for all layers in AutoCAD DXF format on Compact Disc (CD) to the Public Works Department. If the required files are unavailable, the developer shall pay a scanning fee to cover the cost of scanning the as-built plans.</p>	





# Project Conditions

## City of Corona

PUBLIC WORKS	Zachary Murray
<p>10. The developer shall monitor, supervise and control all construction and construction related activities to prevent them from causing a public nuisance including, but not limited to, insuring strict adherence to the following:</p> <ul style="list-style-type: none"> <li>(a) Removal of dirt, debris or other construction material deposited on any public street no later than the end of each working day.</li> <li>(b) Construction operations, including building related activities and deliveries, shall be restricted to Monday through Saturday from 7:00 a.m. to 8:00 p.m., excluding holidays, and from 10:00 a.m. to 6:00 p.m. on Sundays and holidays, in accordance with City Municipal Code 15.04.060, unless otherwise extended or shortened by the Public Works Director or Building Official.</li> <li>(c) The construction site shall accommodate the parking of all motor vehicles used by persons working at or providing deliveries to the site.</li> </ul> <p>Violation of any condition or restriction or prohibition set forth in these conditions shall subject the owner, applicant, developer or contractor(s) to remedies as noted in the City Municipal Code. In addition, the Public Works Director or Building Official may suspend all construction related activities for violation of any condition, restriction or prohibition set forth in these conditions until such time as it has been determined that all operations and activities are in conformance with these conditions.</p> <p>11. Prior to issuance of a building permit, the developer shall finish the construction or post security guaranteeing the construction of all public improvements. Said improvements shall include, but are not limited to, the following:</p> <ul style="list-style-type: none"> <li>a) All street facilities (list the streets/highways by name).</li> <li>b) All drainage facilities (list the channels/storm drains by name or reference them by street).</li> <li>c) All required grading, including erosion control.</li> <li>d) All required sewer, water and reclaimed water facilities.</li> <li>e) All required landscaping and/or park facilities.</li> <li>f) All under grounding of overhead utilities, except for cables greater than 32k volts.</li> </ul> <p>12. All the grading design criteria shall be per City of Corona standards, Corona Municipal Code Title 15 Chapter 15.36 and City Council Ordinance Number 2568, unless otherwise approved by the Public Works Director.</p> <p>13. Prior to approval of grading plans, the applicant shall submit two (2) copies of a soils and geologic report prepared by a Registered Engineer to the Public Works Department Land Development Section. The report shall address the soil's stability and geological conditions of the site. If applicable, the report shall also address: deep seated and surficial stability of existing natural slopes; modified natural slopes which are subject to fuel zones; manufactured slopes and stability along proposed daylight lines; minimum required setbacks from structures; locations and length of proposed bench drains, sub-drains or french drains; and any other applicable data necessary to adequately analyze the proposed development.</p> <p>14. Prior to approval of grading plans, erosion control plans and notes shall be submitted and approved by the Public Works Department Land Development Section.</p> <p>15. Prior to approval of grading plans, the applicant shall obtain a General Construction Activity Storm Water Permit from the State Water Resources Control Board in compliance with National Pollutant Discharge Elimination System (NPDES) requirements. Proof of filing a Notice of Intent (NOI) will be required by the City. The WDID # shall be displayed on the title sheet of the grading plans.</p> <p>16. Prior to approval of grading plans, the applicant shall comply with the Federal Clean Water Act and shall prepare a Storm Water Pollution Prevention Plan (SWPPP). The SWPPP shall be available at the project site for review.</p> <p>17. Prior to issuance of grading permit or construction of any improvements, a letter will be required from a qualified botanist, plant taxonomist or field biologist specializing in native plants, stating that an investigation and/or eradication of scale broom weed (<i>Lepidospartum Squamatum</i>) has been completed.</p> <p>18. Prior to the issuance of a grading permit the developer shall submit recorded slope easements or written letters of permission from adjacent landowners in all areas where grading is proposed to take place outside of the project boundaries.</p> <p>19. Prior to issuance of building permits, the developer shall cause the civil engineer of record and soils engineer of record for the approved grading plans to submit pad certifications and compaction test reports for the subject lots where building permits are requested.</p> <p>20. Prior to release of grading security, the developer shall cause the civil engineer of record for the approved grading plans to submit a set of as-built grading plans with respect to Water Quality Control facilities.</p>	





## Project Conditions City of Corona

### PUBLIC WORKS

Zachary Murray

21. Prior to issuance of any grading permit, any environmental Phase I and Phase II findings and recommended actions to remove contamination resulting from previous use of the subject site shall be implemented.
22. All City of Corona NPDES permit requirements for NPDES and Water Quality Management Plans (WQMP) shall be met per Corona Municipal Code Title 13 Chapter 13.27 and City Council Ordinance Numbers 2291 and 2828 unless otherwise approved by the Public Works Director.
23. Prior to the issuance of a grading permit, a Final WQMP, prepared in substantial conformance with the approved Preliminary WQMP, shall be submitted to the Public Works Land Development Section for approval. Upon its final approval, the applicant shall submit one copy on a CD-ROM in PDF format.
24. Prior to issuance of the first Certificate of Occupancy, the applicant shall provide proof of notification to the future homeowners and/or occupants of all non-structural BMPs and educational and training requirements for said BMPs as directed in the approved WQMP.
25. Prior to issuance of Certificate of Occupancy, the applicant shall ensure all structural post construction BMPs identified in the approved project specific Final WQMP are constructed and operational.
26. Prior to issuance of a grading permit, the project shall incorporate LID Principles (Site Design) and Source Control BMPs, as applicable and feasible, into the project plans for review and approval by the Public Works Department.
27. All the drainage design criteria shall be per City of Corona standards and the Riverside County Flood Control and Water Conservation District standards unless otherwise approved by the Public Works Director.
28. Prior to approval of any improvement plans, the applicant shall submit a detailed hydrology study. Said study shall include the existing, interim and the ultimate proposed hydrologic conditions including key elevations, drainage patterns and proposed locations and sizes of all existing and proposed drainage devices. The hydrology study shall present a full breakdown of all the runoff generated on- and off-site.
29. Street design criteria and cross sections shall be per City of Corona standards, approved Specific Plan design guidelines and the State of California Department of Transportation Highway Design Manual unless otherwise approved by the Public Works Director.
30. Prior to map recordation or issuance of a building permit, whichever comes first, the applicant shall offer for dedication all required street rights-of-way on State Street and Foothill Pkwy. Said dedication shall continue in force until the City accepts or abandons such offers. All dedications shall be free of all encumbrances and approved by the Public Works Director.
31. Prior to approval of improvement plans, the improvement plans submitted by the applicant shall include the following:
  - a) All local and/or major arterial highways' vertical and horizontal alignments shall be approved by the Director of the Public Works Department.
  - b) All driveways shall conform to the applicable City of Corona standards and shall be shown on the street improvement plans.
  - c) All street intersections shall be at ninety (90) degrees or as approved by the Public Works Director.
  - d) All reverse curves shall have a minimum tangent of fifty (50) feet in length.
  - e) Under grounding of existing and proposed utility lines.
  - f) Street lights.
  - g) All other public improvements shall conform to City of Corona standards.
32. Prior to approval of improvement plans, the improvement plans shall show all the streets to be improved to half width plus ten (10) additional feet unless otherwise approved by the Public Works Director. At the discretion of the applicant, the existing pavement maybe cored to confirm adequate section and R values during the design process and any findings shall be incorporated into the project design. Therefore improvements may include full pavement reconstruction, grind and overlay, or slurry seal. All striping shall be replaced in kind.
33. Prior to release of public improvement security, the developer shall cause the civil engineer of record for the approved improvement plans to submit a set of as-built plans for review and approval by the Public Works Department.
34. Prior to acceptance of improvements, the Public Works Director may determine that aggregate slurry, as defined in the Standard Specifications for Public Works Construction, may be required one year after acceptance of street(s) by the City if the condition of the street(s) warrant its application. All striping shall be replaced in kind. The applicant is the sole responsible party for the maintenance of all the improvements until said acceptance takes place.





# Project Conditions

## City of Corona

PUBLIC WORKS	Zachary Murray
	<p>35. The developer is responsible to comply with the approved traffic study recommendations. All fair-share fees shall be paid prior to map recordation. Any public improvements shall be constructed or guaranteed prior to map recordation.</p> <p>36. Prior to map recordation the applicant shall annex this project into a City of Corona Community Facilities District (CFD) 2016-3 (Maintenance Services). All assessable parcels therein shall be subject to annual CFD charges (special taxes or assessments). The developer shall be responsible for all costs incurred during annexation into the CFDs.</p> <p>37. Prior to final map recordation the applicant shall prepare a disclosure statement indicating that the property is within an Assessment District, Community Facilities District and/or Landscape Maintenance District and will be subject to an annual levy. The disclosure statement is subject to the review and approval of the Public Works Department and shall be recorded concurrently with the final map.</p> <p>38. Prior to issuance of a Certificate of Occupancy, all proposed parkway, slope maintenance, and/or median landscaping specified in the tentative map or in these Conditions of Approval shall be constructed.</p> <p>39. Prior to the issuance of a Certificate of Occupancy, any damage to existing landscape easement areas due to project construction shall be repaired or replaced by the developer, or developer's successors in interest, at no cost to the City of Corona.</p> <p>40. Prior to map recordation, issuance of a building permit and/or issuance of a Certificate of Occupancy, the applicant shall pay all development fees, including but not limited to Development Impact Fees (DIF) per City Municipal Code 16.23 and Transportation Uniform Mitigation Fees (TUMF) per City Municipal Code 16.21. Said fees shall be collected at the rate in effect at the time of fee collection as specified by the current City Council fee resolutions and ordinances.</p> <p>41. All the potable water, reclaimed water, and sewer design criteria shall be per City of Corona Department of Water and Power standards and Riverside County Department of Health Services Standards unless otherwise approved by the Public Works and Department of Water and Power Directors.</p> <p>42. Prior to issuance of any building permits, including model home permits, a domestic water and fire flow system shall be approved by the Public Works Department and constructed by the developer, to the satisfaction of the Public Works Director and Fire Chief.</p> <p>43. Prior to issuance of the first Certificate of Occupancy, all weather access road(s) shall be provided to all sewer manholes not located within public right-of-way.</p> <p>44. Prior to improvement plans approval, the applicant shall ensure that all water meters, fire hydrants or other water appurtenances shall not be located within a drive aisle or path of travel.</p> <p>45. Prior to issuance of any building permits, the developer shall pay all water and sewer fees, including but not limited to connection fees, wastewater treatment fees, sewer capacity fees and all other appropriate water and sewer fees.</p> <p>46. Prior to issuance of building permits, the developer shall pay the sewer reimbursement fee for the El Sobrante trunk line if the development is located in the El Sobrante service area.\r\r</p> <p>47. Prior to building permit issuance, the applicant shall construct or guarantee the construction of all required public improvements including but not limited to, the potable water line, sewer line, reclaimed water line, potable water services, sewer laterals, reclaimed water services, double detector check assemblies and reduced pressure principle assemblies within the public right of way and/or easements.</p> <p>48. The applicant shall dedicate easements for all public water, reclaimed water, sewer and electric facilities needed to serve the project in accordance the Department of Water and Power standards. The minimum easement width shall be 20 feet for one utility and 30 feet for more than one public utility facility. All public water and sewer facilities shall be provided a minimum 20 foot wide paved access road unless otherwise approved by the General Manager. Structures and trees shall not be constructed or installed within a public utility easement.</p> <p>49. Prior to map recordation or building permit issuance, whichever comes first, the applicant shall construct or guarantee the construction of a private fire system with double detector check assemblies at all public fire services to the satisfaction of the Department of Water and Power and Fire Chief.</p> <p>50. Fire Hydrants shall be a maximum 250 feet apart or as directed by the Fire Department.</p>



## Project Conditions City of Corona

PUBLIC WORKS	Zachary Murray
<p>51. Manhole rim elevations shall be lower than all pad elevations immediately downstream; otherwise a back flow prevention valve will be required.</p> <p>52. Static pressures exceeding 80 psi require an individual pressure regulator.</p> <p>53. The applicant shall provide a separate irrigation water service for all HOA/ CFD landscaped lots or easements.</p> <p>54. The landscape plans of all parkway and Landscape Maintenance District (LMD) and Community Facilities District (CFD) lots shall be prepared by a licensed Landscape Architect and shall be submitted to the City for review and approval.</p> <p>55. The developer shall install automatic irrigation to all street trees separated from adjacent residences by a fence or wall prior to the issuance of a Certificate of Occupancy.</p>	